STRETCH WRAP, FOAM & SHIPPING SUPPLIES



- Protects product from dust, oil, dirt, and other items while in transit or storage
- Protects product from moisture damage by tightly form fitting to parts
- · Seal to self leaves no residue or marks
- · Reduces labour and cost of packaging
- Simply fold the seal to self over the part and it sticks to itself



| Model | | | Price |
|-------|--------|---------|-------|
| No. | Width" | Length' | /Each |
| PC021 | 7 1/2 | 700 | |
| PC022 | 10 | 700 | |
| PC023 | 15 | 700 | |
| PC024 | 30 | 700 | |

CORRUGATED ROLLS

- Pack and protect shipments with single-faced corrugated paper
- Raised corrugated A fluting provides extra strength and cushioning; tear-resistant protection against breaking, chipping or scratching
- Sturdy, flexible corrugated paper easily conforms to any size and shape
- · Roll diameter: 30"



| Model | Di | Dimensions | | Wt. | Price |
|-------|----|------------|-----|------|-------|
| No. | W" | | | lbs. | /Each |
| PE031 | 12 | Х | 250 | 10 | |
| PE032 | 18 | Х | 250 | 19 | |
| PE033 | 24 | X | 250 | 26 | |
| PE035 | 36 | X | 250 | 34 | |
| PA436 | 48 | Х | 250 | 52 | |
| PE038 | 60 | Х | 250 | 65 | |
| PE040 | 72 | Х | 250 | 68 | |

FLEXIBLE NETTING

- Affordable solution for protecting odd-shaped parts that previously required special packaging
- Constructed of durable, low density polyethylene
- Flexible material conforms to almost any product shape



| Model No. | Description | Flexible Diameters" | Colour | Roll Length' | Price /Each |
|--------------|------------------|------------------------|--------|-----------------|----------------|
| PD086 | Large Close Mesh | 1 1/4 - 1 5/8 | Yellow | 82 | |
| PD087 | Large Close Mesh | 2 - 2 1/2 | Red | 82 | |
| PD088 | Small Close Mesh | 1 - 2 | Yellow | 164 | |
| PD089 | Small Close Mesh | 2 - 4 | Red | 164 | |

COMPACT KNIVES WITH SELF RETRACTING BLADE

- · Heavy-gauge stainless steel blade channel secures blade
- Premium carbon tool steel 18 mm LB blade
- Heavy-duty high-impact ABS plastic handle for better handling
- Blade auto-lock





Model No. PE986 Mfg. No. SK-7 Price/Each \$

REPLACEMENT BLADES

Model No. PE989-10/pkg. Mfg. No. SKB-7/10B Price/Each \$

TILTWATCH® XTR

MONITOR SHIPMENTS THAT MUST REMAIN UPRIGHT

- · Reliable and affordable
- Monitors and controls the shipping attitude of heavy machinery, large batteries, liquids and more
- Indicates red if container has been tilted on its side or completely upended
- · Normal movement or road shock will have no effect
- · Each Tiltwatch® has a unique serial number to prevent tampering
- Vacuum seal eliminates effects of humidity or temperature changes
 Removal of adhesive backing automatically arms device
- Once activated, cannot be reset
- 100/Case

SPECIFICATIONS:

Activation Angle: Monitoring Range: Adhesive: Humidity Tolerances: Temperature Tolerances: 80° ±5% from vertical Single Plane 5 mil high tack acrylic 5% to 99% non-condensing -40°C to 60°C

Composition: Rigid polystyrene housing with stainless steel indicator Size: 2.9" W x 2.7" L x 0.2" D

Installation: Pressure sensitive adhesive or holes to accommodate

Pressure sensitive adhesive or holes to accommodate small screws, nails or staple for rough surfaces

Model No. PE141 Price/Case \$



SHOCKWATCH®

IMPACT DETECTION DEVICES

- 3.8" x 3.8" label affixes easily to packages
- Reacts to impact by changing from clear to red, providing a permanent record of potential damage
- Available in 3 sensitivities (75 to 100 "g" @ 50 millisecs)
- Companion Label PB798 (sold separately), ensures that the consignee knows what to do in the event a Shockwatch* is activated
- Sold per case of 50

SHOCKWATCH® SELECTION GUIDE

| Wt. Ibs. | 0-1 Cubic ft. | 1-5 Cubic ft. | 6-15 Cubic ft. | 16-50 Cubic ft. | 50 Plus Cubic ft. |
|-------------|------------------|------------------|-------------------|--------------------|----------------------|
| 0-10 | Green | Green | Orange | Orange | Red |
| 11-25 | Green | Orange | Orange | Red | Red |
| 26-50 | Orange | Orange | Red | Red | Red |
| 51-100 | Orange | Red | Red | Red | Red |
| 101-250 | Red | Red | Red | Red | - |
| 250-1000 | Red | Red | Red | - | - |

Cubic ft. = Height x Width x Depth

WHERE TO EXPECT LABEL ACTIVATION:

| | Yellow | Red | Orange | Green |
|----------------|--------|--------|--------|----------|
| | (L-65) | (L-47) | (L-35) | (L-30) |
| Under 100 lbs. | - | 12-24" | 24-36" | 36" over |
| Over 100 lbs. | - | 6-12" | 12-18" | - |

Note: The above table and sensor activation trend lines should be used as a guide only. Packaging and construction may affect the correlation between drop height and Shockwatch® activation.

| Model | Mfg. | | Sensitivity | Qty | Price |
|-------|-------|-------------|-------------|-------|-------|
| No. | No. | Description | g Force | /Case | /Case |
| PC438 | 20100 | Green | 100 | 50 | |
| PC439 | 20300 | Orange | 75 | 50 | |
| PC440 | 20500 | Red | 50 | 50 | |

MULTILINGUAL COMPANION LABELS

| Model | Dimensions" | Qty | Price |
|-------|-------------|-------|-------|
| No. | | /Case | /Case |
| PB798 | 5 x 8 | 200 | |

