

DRUM PUMPS & PUMPS

SMALL SUBMERSIBLE OIL FILLED PUMPS

- 1/160 HP oil-filled motor, 115 V, 60 Hz, 0.5 A
- Corrosion resistant nylon body
- 4.6' maximum lift
- 1/4" MNPT discharge
- Intermittent liquid temp up to 120 °F
- 10' power cord length
- For submersible use only

Model No. DA342
Price/Each \$



Little GIANT
PUMP COMPANY

5.5 SERIES SUMP PUMP

- PSC motor with thermal overload protection
- Integral snap-action float switch
- 1-1/2" discharge
- 3/4" GHT (19mm) garden hose adapter included
- Screened inlet handles up to 3/8" (9.5 mm) solids
- 120 °F (49 °C) liquid temperature rating
- cCSAus listed
- Motor: 1/4 HP
- Max. Flow Rate: 35 GPM
- Voltage: 115 V
- Amps: 3.5 A
- Cord Length: 10' (3 m)
- Manufacturer's Warranty: 3 Years

Model No. UAK135
Price/Each \$



Little GIANT
PUMP COMPANY

9EC SERIES EFFLUENT PUMP

- Permanent Split Capacitor (PSC)
- Designed for continuous duty
- Energy-saving low amp draw
- 1-1/2" FNPT (38 mm) discharge
- Handles solids up to 3/4" (19 mm) diameter
- Piggyback float switch
- 140 °F (60 °C) liquid temperature rating
- cCSAus listed
- Motor: 4/10 HP
- Max. Flow Rate: 70 GPM
- Voltage: 115 V
- Amps: 7.5 A
- Cord Length: 20' (6.1 m)
- Manufacturer's Warranty: 3 Years

Model No. UAK146
Price/Each \$



Little GIANT
PUMP COMPANY

HIGH TEMPERATURE SUMP/EFFLUENT PUMPS

- 1/3 HP, 115 V, 60 Hz, 10.1 A
- Handles liquids up to 200 °F and solids up to 1/2"
- Cast iron pump housing with protective epoxy coating for corrosion resistance
- Oil-filled motor housing for lifetime lubrication and rapid heat dissipation
- Integral mechanical float switch
- Stainless steel screws, bolts and lifting ring to protect against corrosion
- Bearings: Upper and lower sintered sleeve bearings for extended motor life
- 15' Power cord
- Thermal overload protection
- Automatic operation has 10" to 12" "On" level range

Model No. DA336
Price/Each \$



Little GIANT
PUMP COMPANY

AUTOMATIC SWITCHES

- Converts manual pump up through 1/2 HP to automatic operation
- Turns on at 6 - 9" and off at 1 - 4"
- 18' power cord
- CSA listed

Model No. DA357
Price/Each \$



Little GIANT
PUMP COMPANY

SUBMERSIBLE SUMP PUMPS

- 1/6 HP shaded pole motor with overload protection, 115 V, 60 Hz, 5 A
- Designed for continuous duty
- Pumps down to 1/8"
- Epoxy coated cast aluminum housing, Viton® shaft seal
- 18' power cord length
- Includes: garden hose adapter and removable inlet screen for easy cleaning

Model No. DA332
Price/Each \$



Little GIANT
PUMP COMPANY

SUBMERSIBLE PUMPS

- 1/3 HP shaded pole motor, 115 V, 9 A
- 1/2" 1-1/4" FNPT x 1-1/2" MNPT adapter
- Cast iron pump housing with protective epoxy coating for corrosion resistance
- Oil-filled motor housing for lifetime lubrication and rapid heat dissipation
- Stainless steel screws, bolts and handle to protect against corrosion
- Bearings: Upper and lower sintered sleeve bearings for extended motor life
- 8' Power cord
- Thermal overload protection
- Automatic operation with pressure switch activates pump when water level is between 7" and 10"
- Pump shuts off when water level falls to between 1" and 4"

Model No. DA334
Price/Each \$



Little GIANT
PUMP COMPANY

SUMP/EFFLUENT PUMPS

- 1/3 HP shaded pole motor, 115 V, 5 A
- Handles liquid and solid waste materials up to 1/2" diameter
- Cast iron pump housing with protective epoxy coating for corrosion and rust resistance
- Oil-filled motor housing for lifetime lubrication and rapid heat dissipation
- Stainless steel screws, bolts and handle
- Bearings: Upper and lower sintered sleeve bearings
- 10' Power cord
- Thermal overload protection
- Automatic operation has 8" to 11" "On" level range and 2" to 5" "Off" level range
- Integral snap action float switch
- Base material: Polypropylene

Model No. DC431
Price/Each \$



Little GIANT
PUMP COMPANY

ELECTRIC SEWAGE PUMP

- Features a permanent split capacitor, energy-saving low amp draw, and multiple switch options for automatic operation
- Designed for continuous duty
- Handles solids up to 2" diameter
- Motor: 1/2 HP
- Max. Flow Rate: 120 GPM
- Voltage: 115 V
- Amps: 11 A
- Max. Diameter of Waste: 2"
- Liquid Temperature Rating: 140 °F (60 °C)
- Switch Type: Piggyback Mechanical Float
- Max. Flow Rate @ 10 ft: 100 GPM
- Max. Flow Rate @ 15 ft: 80 GPM

Model No. DC818
Price/Each \$



FLOW CHART:

Model No.	Performance (GPM @ Head)					
	1'	3'	5'	10'	15'	20'
DA342	2	1.16	-	-	-	-
DA334	-	-	46	29	12.5	-
DA332	20	19.5	18.3	16.6	-	8.6
DC431	-	-	50	42	30	-
DA336	-	-	50	42	27	-