

# CHEMICALS

## MR311 DRY FILM RELEASE AGENT

- Non-silicone mould release
- Exceptional anti-stick properties that will not transfer to finished parts allowing for multiple releases per application
- Compatible with most mouldable resins, elastomeric compounds, urethanes and styrenes
- Will not attack rubber, paints or metals
- Recommended for low and high-temperature moulds up to 575°F
- For polystyrenes, polypropylenes, nylon, rubber, foams, metals, filament windings, polyurethanes, epoxy potting and encapsulating and phenolic resins
- NSF Certified



Model No.	Mfg. No.	Size	Price /Each
AA174	SC0311000	12 oz.	

## BELT DRESSING

- Does not contain 1,1,1 or any harmful, chlorinated solvents that deteriorate drive belts
- Low odour
- Prevents belt slippage on flat, round and V-belts
- Fast evaporation
- Eliminates squeaks from slipping belts
- Resists wash-off
- Extends belt life and pulley bearing life
- Can be used in wet outdoor conditions
- Made of FDA compliant materials
- NSF registered category code H1
- Accepted for use in Canadian food processing facilities
- Metal and x-ray detectable plastic aerosol components



Model No.	Mfg. No.	Size	Price /Each
AA869	C02216	10 oz.	

## YELLOW 77® WIRE PULLING LUBRICANT

- Wax-based formula provides superior lubricity
- Safe to use with most cable types except low-density polyethylene and semi-conducting jackets
- Clings to cable through long pulls
- Environmentally safe - non-toxic, non-flammable, non-corrosive
- Dries to a thin, non-conductive film that won't clog conduit



Model No.	Description	Price /Each
AB488	1 qt. Squeeze Bottle	
AB489	1 gal. Tub	

## LU767 INDOOR METAL PROTECTANT

- Non-staining, medium-weight oil formulated for long-term indoor protection
- Penetrates, displaces moisture and prevents rust
- Works up to 15 months against humidity and corrosion damage
- Leaves an amber film to identify coverage
- Contains no silicone or chlorinated solvents
- Safe to use on metals, rubber, and most plastic and painted surfaces
- Protects equipment stored indoors and items waiting to be shipped



Model No.	Mfg. No.	Size	Price /Each
AA228	SC0767000	10 oz.	

## COLOR GUARD® TOUGH RUBBER COATING

- Inhibits rust and corrosion
- Seals, insulates, and identifies almost any material in minutes
- Creates a non-slip gripping surface
- Rubber coating won't crack or chip
- Acid and alkali resistant
- Lasts for years
- Use to 200°F
- For dip, spray, or brush
- For tools, metal, electrical connections, masonry, wood, conveyors, glass, rope, fabric
- Toluene-free



Model No.	Mfg. No.	Size	Colour	Price /Each
AC013	338124	14.5 oz.	Black	
AC014	338125	1 gal.	Black	
AC016	338127	14.5 oz.	Blue	
AC017	338128	1 gal.	Blue	
AC011	338130	14.5 oz.	Red	
AC012	338131	1 gal.	Red	
AC159	338133	14.5 oz.	Yellow	
AC015	338134	1 gal.	Yellow	

## SF 7900™ CERAMIC SHIELD FOR WELDING

- Ceramic dry film protective coating for MIG/MAG welding processes
- Protects contact tips and welding nozzles by preventing adhesion of welding spatter
- Once applied the coating dries by solvent evaporation within 5 to 10 seconds at room temperature (Thicker films will need longer drying time)
- Ceramic, silicone-free protective coating, easy to apply
- Protects contact tips, welding nozzles and jigs, eliminating cost for cleaning equipment
- Reduces running costs for consumables by up to 40%
- Prevents adhesion of welding spatter for many hours with just one application
- Colour: White



Model No.	Mfg. No.	Size	Price /Each
AD492	1616692	9.5 oz.	

## SF7607™ RUBBERIZED UNDERCOATING

- Heavy-duty undercoating seals, protects, and insulates
- Rubberized for maximum durability



Model No.	Mfg. No.	Size	Price /Each
AA635	234926	16 oz.	