



## 1/4" AIR SCREWDRIVERS

- Durable steel body
- Forward-reverse switch
- Low noise, low vibrations
- Overall length: 7 1/2"
- Weight: 2.4 lbs.



<b>Model No.</b>	<b>TLV495</b>
<b>Air Consumption</b>	6 CFM
<b>Air Inlet:</b>	1/4"-18 NPT
<b>Sound Level (dBA)</b>	82
<b>No Load RPM</b>	1800
<b>Torque Range ft.-lbs.</b>	3.75-9.5
<b>Hose Size</b>	3/8" (9.5 mm)
<b>Horse Power</b>	0.5
<b>Vibrations Less than m/s<sup>2</sup></b>	0.7
<b>Price/Each</b>	\$

**AURORA**  
TOOLS

## DIRECT DRIVE REVERSIBLE SCREWDRIVER

<b>Model No.</b>	<b>UAG274</b>
<b>Mfg. No.</b>	GS-1017Q
<b>Clutch Type</b>	Keyless / Direct Drive Reversible
<b>Handle style</b>	Pistol grip
<b>Operation</b>	Trigger start
<b>Torque range</b>	216-312 in.-lbs.
<b>Length</b>	5.6" (142 mm)
<b>Weight</b>	1.98 lbs (0.9 kg)
<b>Air Consumption</b>	28 CFM
<b>Air Inlet</b>	1/4" NPTF
<b>Air Hose Bore</b>	3/8"
<b>Sound Level (dBA)</b>	88
<b>Vibration Level</b>	<2.5 m/s <sup>2</sup>
<b>Price/Each</b>	\$



**AURORA**  
TOOLS

## DIRECT DRIVE REVERSIBLE SCREWDRIVERS

- Suitable for variable torque
- High speed fast screw rundown
- Ergonomic pistol grip improves operator comfort and productivity

<b>Model No.</b>	<b>TLZ339</b>
<b>Mfg. No.</b>	CP2755
<b>Clutch Type</b>	Direct drive reversible
<b>Handle style</b>	Pistol grip
<b>Operation</b>	Trigger start
<b>Free Speed</b>	2200 RPM
<b>Output</b>	Hex. 1/4"
<b>Torque range</b>	124 in.-lbs.
<b>Length</b>	6.3"
<b>Weight</b>	2.27 lbs.
<b>Air Flow</b>	29 CFM
<b>Air Inlet</b>	1/4" NPTF
<b>Air Hose Bore</b>	3/8"
<b>Sound Level</b>	90 dBA
<b>Vibration Level</b>	<2.5 m/s <sup>2</sup>
<b>Price/Each</b>	\$



**Chicago Pneumatic™**

## POSITIVE CLUTCH REVERSIBLE SCREWDRIVERS

- Quick change chuck
- Operator can force clutch engagement for higher torque
- Reverse control at the trigger
- Good for prevailing torque applications
- High speed and high torque

<b>Model No.</b>	<b>TLZ340</b>
<b>Mfg. No.</b>	CP2780
<b>Clutch Type</b>	Positive clutch
<b>Handle style</b>	Pistol grip
<b>Operation</b>	Trigger start
<b>Free Speed</b>	2100 RPM
<b>Output</b>	Hex. 1/4"
<b>Torque range</b>	133 in.-lbs.
<b>Length</b>	6.46"
<b>Weight</b>	2.35 lbs.
<b>Air Flow</b>	29 CFM
<b>Air Inlet</b>	1/4 NPTF
<b>Air Hose Bore</b>	3/8"
<b>Sound Level</b>	89 dBA
<b>Vibration Level</b>	26.8 m/s <sup>2</sup>
<b>Price/Each</b>	\$



**Chicago Pneumatic™**

## 19 SERIES - STALL SCREWDRIVERS

- Tool weight: 1.16 lbs.
- Tool length: 5.9"
- Free speed: 1100 RPM
- Max Torque: 40 in.-lbs.
- Engineered for heavy duty applications in the most demanding environment
- Adjustable reverse lever for true one-hand - left-handed or right-handed - operation
- Trigger start
- "P" handle style
- Interchangeable soft-touch grip sizes
- Air consumption: 11 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- Chuck Type: Keyless

**Model No. TYN249**  
**Mfg. No. 19PTS04Q**  
**Price/Each \$**



**Cleco®**

## 19 SERIES - PISTOL GRIP SCREWDRIVERS W/ADJUSTABLE TORQUE SETTINGS

- Tool weight: 1.41 lbs.
- Tool length: 8.0"
- Free speed: 1100 RPM
- Max Torque: 40 in.-lbs.
- Engineered for heavy duty applications in the most demanding environment
- Class-leading accuracy and repeatability
- Adjustable reverse lever for true one-hand - left-handed or right-handed - operation
- "P" handle style
- Interchangeable soft-touch grip sizes
- Trigger and Push & Trigger start
- External torque adjustment from 10 - 40 in.-lbs.
- Air consumption: 11 CFM
- Air inlet: 1/4"
- Sound level (dBA): 80
- Chuck Size: 1/4"
- Chuck Type: Keyless

**Model No. TYN248**  
**Mfg. No. 19PTA04Q**  
**Price/Each \$**



**Cleco®**